



Item # _____

Job _____

SUPER ERECTA SHELF® SOLID SHELVING (18-Gauge)

- **Strength:** Two-fold thickness of 18-gauge steel forms 1/8" (3.2mm) raised edges on all four sides of the shelving. This ship's edge gives all-around rigidity and high strength.
- **Sanitary:** Flat, solid style with the raised ship's edge on all four sides and at the corners contains spills, minimizes contamination and permits easier clean-up. Louvered/embossed shelf design allows air circulation under packages and containers.
- **Galvanized Shelves** with uncoated cast corners are ideal for applications requiring solid shelving or a work surface and minimum resistance to corrosion. Available in flat solid and louvered/embossed styles.
- **Standard Type 304 Stainless Steel** shelves with epoxy-coated cast corners address the majority of applications for solid, corrosion resistant shelves or work surfaces. Available in flat solid and louvered/embossed styles.
- **Premium Autoclave/Cart Washable Type 304 Stainless Steel** solid shelves feature an all-stainless construction to withstand high temperature, corrosive applications. Available in flat solid style.
- **Versatile Construction:** Super Erecta Shelf® solid shelving can change as quickly as your needs change. By using various accessories hundreds of shelving configurations become possible.
- **Shelf Accessibility:** Shelves can be loaded/unloaded from all sides. This open construction allows use of the maximum storage space of the cube.
- **Adjustability:** Shelves can be adjusted in 1" (25mm) intervals along the entire length of the post.
- **Adjustable Feet:** Leveling bolts compensate for surface irregularities. Note: Stainless steel stationary posts include stainless leveling bolts.



Raised Ship's Edge



SUPER ERECTA SHELF®
Solid Shelving (18-Gauge)

*MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban Products Company, Huntersville, NC.



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com



10-20



SUPER ERECTA SHELF® SOLID SHELVING (18-Gauge)

Galvanized shelves have uncoated, cast aluminum corners. Standard Type 304 Stainless Steel shelves have black epoxy-coated corners. Autoclavable/cart washable Type 304 Stainless Steel shelves have stainless corners.

Nominal Width/Length (in.) (mm)		Approx. Pkd. Wt. (lbs.) (kg)		GALVANIZED		STAINLESS STEEL		Autoclavable Cart Washable Stainless Steel
				Flat Galvanized	Louvered/ Embossed Galvanized	Flat Stainless	Louvered/ Embossed Stainless	Flat Stainless
14x24	355x610	10	4.5	1424FG	1424LG	1424FS	1424LS	1424NFS
14x30	355x760	12	5.4	1430FG	1430LG	1430FS	1430LS	1430NFS
14x36	355x914	14	6.4	1436FG	1436LG	1436FS	1436LS	1436NFS
14x42	355x1066	15	6.8	1442FG	1442LG	1442FS	1442LS	1442NFS
14x48	355x1219	17	7.7	1448FG	1448LG	1448FS	1448LS	1448NFS
14x60	355x1524	22	9.9	1460FG	1460LG	1460FS	1460LS	1460NFS
18x24	457x610	11	5.0	1824FG	1824LG	1824FS	1824LS	1824NFS
18x30	457x760	14	6.4	1830FG	1830LG	1830FS	1830LS	1830NFS
18x36	457x914	16	7.3	1836FG	1836LG	1836FS	1836LS	1836NFS
18x42	457x1066	18	8.2	1842FG	1842LG	1842FS	1842LS	1842NFS
18x48	457x1219	20	9.1	1848FG	1848LG	1848FS	1848LS	1848NFS
18x60	457x1524	24	10.9	1860FG	1860LG	1860FS	1860LS	1860NFS
18x72	457x1829			*	—	*	—	—
21x24	530x610	13	5.9	2124FG	2124LG	2124FS	2124LS	2124NFS
21x30	530x760	15	6.8	2130FG	2130LG	2130FS	2130LS	2130NFS
21x36	530x914	18	8.2	2136FG	2136LG	2136FS	2136LS	2136NFS
21x42	530x1066	21	9.5	2142FG	2142LG	2142FS	2142LS	2142NFS
21x48	530x1219	23	10.4	2148FG	2148LG	2148FS	2148LS	2148NFS
21x60	530x1524	26	11.8	2160FG	2160LG	2160FS	2160LS	2160NFS
24x24	610x610	15	6.8	2424FG	2424LG	2424FS	2424LS	2424NFS
24x30	610x760	17	7.7	2430FG	2430LG	2430FS	2430LS	2430NFS
24x36	610x914	19	8.6	2436FG	2436LG	2436FS	2436LS	2436NFS
24x42	610x1066	21	9.5	2442FG	2442LG	2442FS	2442LS	2442NFS
24x48	610x1219	24	10.9	2448FG	2448LG	2448FS	2448LS	2448NFS
24x60	610x1524	31	14.0	2460FG	2460LG	2460FS	2460LS	2460NFS
24x72	610x1829			*	—	*	—	—

*Contact your Metro representative for availability.



SiteSelect Posts for Super Erecta® Solid Shelving

Stationary posts are fitted with adjustable leveling bolts to compensate for uneven surfaces. Mobile posts will accept stem casters (see Cat. Sheet 11.20). Height for stationary units includes leveling bolt and cap.

STATIONARY				MOBILE				Approx. Pkd. Wt.	
Actual Height* (in.) (mm)	Model No. Plated	Model No. Stainless	Actual Height* (in.) (mm)	Model No. Plated	Model No. Stainless	(lbs.)	(kg)		
7 ³ / ₈	187	7P	7PS	6 ³ / ₄	171	7UP	7UPS	1/2	0.3
14 ³ / ₈	365	13P	13PS	13 ³ / ₄	349	13UP	13UPS	1	0.5
28 ³ / ₈	720	27P	27PS	27 ³ / ₄	704	27UP	27UPS	1 ³ / ₄	0.75
34 ³ / ₈	873	33P	33PS	33 ³ / ₄	857	33UP	33UPS	2	0.9
54 ⁷ / ₁₆	1382	54P	54PS	53 ¹³ / ₁₆	1366	54UP	54UPS	3	1.4
62 ⁷ / ₁₆	1585	63P	63PS	61 ¹³ / ₁₆	1570	63UP	63UPS	3 ¹ / ₂	1.6
—	—	—	—	69 ³ / ₄	1771	70UP	—	3 ³ / ₄	1.7
74 ¹ / ₂	1892	74P	74PS	73 ⁷ / ₈	1876	74UP	74UPS	4	1.8
86 ¹ / ₂	2197	86P	86PS	85 ⁷ / ₈	2181	86UP	86UPS	4 ¹ / ₂	2.0
96 ¹ / ₂	2450	**96P	96PS	—	—	—	—	5 ¹ / ₂	2.5

*Actual height for the stationary post includes the post cap and the leveling bolt completely tightened.

SiteSelect Posts for Autoclavable/ Cart-Washable Applications



9986S

Designed for use with stem casters and fitted with swedged aluminum post caps.

Actual Height (in.) (mm)	Approx. Pkd. Wt. (lbs.) (kg)	Model No. Stainless Steel	
33 ³ / ₄	857	2 0.9	33UPS-SW
53 ¹³ / ₁₆	1366	3 1.4	54UPS-SW
61 ¹³ / ₁₆	1570	3 ¹ / ₂ 1.6	63UPS-SW

Order aluminum split sleeves with stainless "C" rings or corrosive, high-temperature autoclave or cart washing applications.
Model No. **9986S**
One bag required per shelf.

All Metro Catalog Sheets are available on our Web Site: www.metro.com



InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705
Phone: 570-825-2741 • Fax: 570-825-2852

For Product Information:

U.S. and Canada: 1-800-992-1776

Outside U.S. and Canada: www.metro.com/contactus

L02-014

Printed in U.S.A. Rev. 4/11

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2011 InterMetro Industries Corp.